

The Queensland State Emergency Service (SES) provides tarps for your roof to temporarily protect your home from the elements. If your home has been tarped by SES volunteers, the following instructions will assist you in re-tying and tightening existing tarp knots.

Please do not climb up trees or on roofs to adjust your tarp.

To secure a tarp to a tie-off point use a 'round turn and two half-hitches' knot. This simple knot keeps the tension on the tarping rope whilst being tied. Make sure there is firm tension on the tarping rope but not so tight that your risk pulling the eyelets out of the tarp.

FLOOD STORM 132 500 EMERGENCY SES Assistance QLD Mobile App









To tie a 'round turn and two half hitches' knot

Form a round turn by passing the rope twice around the tie-off point and pull on the end of the rope to tension the tarp. Hold the tension.



Form a second half hitch by repeating step two.



Form a half hitch by



Pull tight to complete the knot.





How to choose a tie-off point

Ensure what you use as a tie-off point is secure. Give it a good shake first. If it moves, look for something else.

Some examples include:

- >> Fences secure posts/rails, rather than palings
- >> Clotheslines the centre upright post
- >> Railings on balconies or patios check for rust
- >> House stumps or trees

If the tarping rope crosses a path or regular walking area, tie a piece of bright cloth to it so it can be easily seen day or night.

Do not tie the tarp to vehicles or downpipes.

qfes.qld.gov.au



© State of Queensland (Queensland Fire and Emergency Services) 2022
All Queensland Fire and Emergency Services material in this document — except any material protected by a trademark, and unless otherwise noted — is licensed under a Creative Commons Attribution 4, oi licence.